



## SPECIFICATION

| Model NO.         | LIRDNHTC200F            | LIRDNCHT200F            | LIRDNTHC200F            |
|-------------------|-------------------------|-------------------------|-------------------------|
| Video Output Mode | AHD/CVI/TVI/CVBS 4 IN 1 | CVI/AHD/TVI/CVBS 4 IN 1 | TVI/AHD/CVI/CVBS 4 IN 1 |

### Camera

|                    |                                   |
|--------------------|-----------------------------------|
| Image Sensor       | 1/2.9" CMOS Sensor                |
| Image Resolution   | 2MP 1080P/ 960H                   |
| Effective Pixels   | 1920*1080                         |
| TV System          | PAL/NTSC                          |
| Electronic Shutter | 1/25s~1/50,000s , 1/30s~1/60,000s |
| S/N Ratio          | ≥50dB                             |
| Scanning System    | Progressive Scan                  |

### Lens

|                   |                            |
|-------------------|----------------------------|
| Focus Length      | 3.6mm (2.8mm/6mm Optional) |
| Focus Control     | Fixed                      |
| Lens Type         | Fixed                      |
| Pixels            | 5M Pixels                  |
| Auto Iris Support | NO                         |

### Night Vision

|                   |                     |
|-------------------|---------------------|
| Infrared LED      | 14μ x 18PCS         |
| Infrared Distance | 20M                 |
| IR Status         | Under 10 Lux by CDS |
| IR Power On       | CDS Auto Control    |

### Camera Features

|                    |               |
|--------------------|---------------|
| Starlight          | /             |
| Day/Night          | YES           |
| OSD Menu Language  | YES           |
| White Balance      | AUTO / MANUAL |
| Gain Control       | AUTO          |
| Noise Reduction    | 3DNR          |
| Picture Adjustment | YES           |
| WDR                | YES           |
| OSD Support        | YES           |
| UTC                | YES           |
| Dip Switch         | Optional      |

### General

|                       |                         |
|-----------------------|-------------------------|
| Housing               | Metal, IP66             |
| Bracket               | NO                      |
| Dual Voltage          | NO                      |
| IR Cut Filter         | YES                     |
| Heater                | NO                      |
| Audio                 | Optional                |
| Operation Temperature | -10°C ~ +50°C RH95% Max |
| Storage Temperature   | -20°C ~ +60°C RH95% Max |
| Power Source          | DC12V±10%, 550mA        |
| Dimension             | ∅ 94.5 x 76(H) mm       |
| Weight                | 450g                    |