

# LIN60S200



| SPECIFICATION           |                                                                                                                                                                                 |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model NO.               | LIN60S200                                                                                                                                                                       |
| Camera                  |                                                                                                                                                                                 |
| Image Sensor            | 1/2.9" SONY Low Illumination CMOS Sensor                                                                                                                                        |
| Resolution              | 2MP 1080P                                                                                                                                                                       |
| Effective Pixels        | 1985(H)*1105(V)                                                                                                                                                                 |
| Compression             | H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG                                                                                                                                       |
| TV System               | PAL/NTSC                                                                                                                                                                        |
| Electronic Shutter Time | Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec                                                                                                                                 |
| S/N Ratio               | ≥52dB                                                                                                                                                                           |
| Scanning System         | Progressive                                                                                                                                                                     |
| Video Output            | Network                                                                                                                                                                         |
| Reset Button            | Optional                                                                                                                                                                        |
| Lens                    |                                                                                                                                                                                 |
| Focus Length            | 2.8-12mm                                                                                                                                                                        |
| Focus Control           | Manual                                                                                                                                                                          |
| Lens Type               | Varifocal                                                                                                                                                                       |
| Pixels                  | 3MP                                                                                                                                                                             |
| Night Vision            |                                                                                                                                                                                 |
| Infrared LED            | 42μ x 4PCS                                                                                                                                                                      |
| Infrared Distance       | 40M                                                                                                                                                                             |
| IR Status               | Under 10 Lux By CDS                                                                                                                                                             |
| IR Power On             | CDS Auto Control                                                                                                                                                                |
| Network                 |                                                                                                                                                                                 |
| Ethernet                | RJ-45 (10/100Base-T)                                                                                                                                                            |
| Protocol                | TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP                                                                                                                 |
| ONVIF                   | Support ONVIF 2.4                                                                                                                                                               |
| P2P                     | YES, Support QR Code                                                                                                                                                            |
| POE                     | Optional, Support IEEE 802.3af                                                                                                                                                  |
| Video Delay             | 0.3S (Within the Lan)                                                                                                                                                           |
| Main Stream 1           | 1920*1080@30fps                                                                                                                                                                 |
| Main Stream 2           | 1280*720@30fps                                                                                                                                                                  |
| Main Stream 3           | /                                                                                                                                                                               |
| Sub Stream 1            | 720*480@30fps                                                                                                                                                                   |
| Sub Stream 2            | /                                                                                                                                                                               |
| Sub Stream 3            | /                                                                                                                                                                               |
| Tri Stream              | 352*288@30fps                                                                                                                                                                   |
| IE Brower               | IE8-11, Google Chrome, Firefox, Safari, Mac Safari                                                                                                                              |
| Smart Phone             | iPhone, iPad, Android, Android Pad                                                                                                                                              |
| Camera Features         |                                                                                                                                                                                 |
| Day/Night               | Color/ B&W (IR-CUT )                                                                                                                                                            |
| Image Config            | Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)                                                                                  |
| Starlight               | /                                                                                                                                                                               |
| Corridor Pattern        | /                                                                                                                                                                               |
| Defog Mode              | Support                                                                                                                                                                         |
| ROI                     | Support                                                                                                                                                                         |
| BLC                     | Support                                                                                                                                                                         |
| HDR                     | /                                                                                                                                                                               |
| WDR                     | Support                                                                                                                                                                         |
| Motion Detection        | Support                                                                                                                                                                         |
| Privacy Masking         | 3 Rectangular Zone                                                                                                                                                              |
| Recording Mode          | NVR/NAS/CMS/Web                                                                                                                                                                 |
| Language                | Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands |
| Interface               |                                                                                                                                                                                 |
| Audio                   | Optional                                                                                                                                                                        |
| Alarm                   | /                                                                                                                                                                               |
| SD Card Slot            | Optional, Support Max 128GB                                                                                                                                                     |
| RS485                   | /                                                                                                                                                                               |
| General                 |                                                                                                                                                                                 |
| Housing                 | Metal , IP66                                                                                                                                                                    |
| Anti-cut Bracket        | YES                                                                                                                                                                             |
| IR Cut Filter           | YES                                                                                                                                                                             |
| Operation Temperature   | -20℃ ~ +60℃ RH95% Max                                                                                                                                                           |
| Storage Temperature     | -20℃ ~ +60℃ RH95% Max                                                                                                                                                           |
| Power Source            | DC12V±10%, 1000mA                                                                                                                                                               |
| Dimension               | 275(W) x 91(H) x 80(D)mm                                                                                                                                                        |
| Weight                  | 1400g                                                                                                                                                                           |